



## General info

### Technical - Systems

|              |                                |
|--------------|--------------------------------|
| Ean          | 8021696317953                  |
| Item         | EGO ACCENT 13W 4000K ON-OFF BK |
| Installation | Systems                        |
| Guarantee    | 5 years                        |
| Gross weight | 0.19 kg                        |
| Volume       | 0.001254 m³                    |

## Technical info

|                          |                                       |
|--------------------------|---------------------------------------|
| Net weight               | 0.14 kg                               |
| Insulation class         | III                                   |
| Protection index         | IP20                                  |
| Compliance               | CE                                    |
| Operating temperature    | 0° ~ +40 °C                           |
| Dimmer                   | NO, On-Off                            |
| Power output             | 48 V DC                               |
| Power supply             | Required, remoted, not included<br>NO |
| Adjustability            | vert. 0°-90°                          |
| Accessories not included | Ego profile                           |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 13 W                                      |
| Emission               | Direct                                    |
| Max consupcion         | max 13,00 W                               |
| Features LED           | LED SMD OSRAM                             |
| CCT LED                | 4000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3                                         |
| Light beam             | 35°                                       |
| UGR Maximum            | < 19                                      |
| Light beam flux        | 1350 lm                                   |
| Useful light flux      | 1240 lm                                   |
| Photobiological risk   | 1                                         |