


## General info

## Outdoor - Floor lamps



|              |                          |
|--------------|--------------------------|
| Ean          | 8021696322537            |
| Item         | STYLE PT H050 NERO 3000K |
| Installation | Floor lamps              |
| Guarantee    | 5 years                  |
| Gross weight | 1.02 kg                  |
| Volume       | 0.012167 m³              |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 1.02 kg                                                                        |
| Insulation class      | I                                                                              |
| Protection index      | IP54                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | -15° ~ +45 °C                                                                  |
| Dimmer                | NO, On-Off                                                                     |
| Power output          | 100-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | 9 W                   |
| Emission               | Direct                |
| Max consupcion         | max 9,00 W            |
| Features LED           | LED SMD               |
| CCT LED                | 3000 K                |
| Duration LED (t. 25°C) | 30000 h               |
| CRI                    | > 80                  |
| Light beam             | 120°                  |
| Light beam flux        | 1050 lm               |
| Useful light flux      | 790 lm                |